

**MACHINE SPECIFICATIONS 05-2018**

\*Specifications subject to change without notice.

<b>MODEL</b>	<b>SW2044-OS</b>	<b>SW2044-HT</b>
<b>WORK CAPACITY</b>		
HEIGHT	44"	44"
ROLLOUT TURNTABLE	20"	20"
LOAD WEIGHT CAPACITY	500	500
<b>FLOOR SPACE REQUIRED</b>		
HEIGHT	80"	80"
WIDTH	48"	55"
LENGTH: DOOR OPEN	83"	83"
DOOR CLOSED	44"	60"
LOADING HEIGHT	27"	27"
<b>CLEANING SYSTEM</b>		
SOLUTION CAPACITY	55 gals.	80 gals.
PUMP MOTOR	5 HP	5 HP
PUMP OUTPUT	(50 psi @ 80gpm)	(50 psi @ 80gpm)
SPRAYNOZZLES	23	23
MANIFOLD SIZE	1.5" WELDED	1.5" WELDED
MANIFOLD CONFIGURATION	360	360
FILTER SCREEN	695 sq."	1290 sq."
TURNTABLE DRIVE	GEAR DRIVE	GEAR DRIVE
<b>CABINET CONSTRUCTION</b>		
GAUGE STEEL	12 gauge	12 gauge
STEAM VENT	6"	6"
GAS VENT	n/a	n/a
DOOR DESIGN	LAY DOWN	LAY DOWN
DOOR SEALS	NONE	NONE
<b>HEAT SOURCE</b>		
ELECTRIC ELEMENT	7.5 KW	10 KW
GAS BURNER	n/a	n/a
<b>HOT TANK BASKETS</b>		
WIDTH (I.D.)	11"	21"
LENGTH (I.D.)	24"	30"
DEPTH (I.D.)	11"	11"
<b>ELECTRICAL REQ.</b>		
PUMP MOTOR 3 PHASE AMP DRAW	208 / 230 / 460 Volts 13 12 6.0 Amps	
ELECTRIC HEAT 3 PHASE AMP DRAW	(7.5 KW) 208/230/460 Volts 21-19-10 Amps	(10 KW) 208/230/460 Volts 28-25-13 Amps
<b>*ELECTRICAL OPTIONS</b>		
5 HP PUMP MOTOR 1 PHASE	230 Volts, 21 Amps	
ELECTRIC HEATER 1 PHASE	(7.5KW) 230 Volts 33 Amps	(10 KW) 230 Volts 44 Amps
Shipping Weight	875	1200
<b>STANDARD EQUIPMENT</b>		
LOW WATER SWITCH	STANDARD	
DUAL 7 DAY TIMERS	STANDARD	
DIGITAL TEMP CONTROLLER	STANDARD	
ADJUSTABLE HEAD RACK/CRANK RACK	STANDARD	
AUTO AIR INDUCER	STANDARD	
SHORT CIRCUIT PROTECTION	STANDARD	
THERMAL PROTECTION	STANDARD	
LAY DOWN DOOR/SEALESS	STANDARD	
V-BOTTOM FLOOR	STANDARD	
BUILT IN HOT TANK	STANDARD	
360 DEGREE MANIFOLD	STANDARD	