

MACHINE SPECIFICATIONS

*Specifications subject to change without notice.

MODEL	SW-2832R	SW-2832HT	SW-2832EX
WORK CAPACITY			
HEIGHT	32"	32" '1	32"
TURNTABLE DIA.	28"	28"	28"
LOAD WEIGHT CAPACITY	700 LBS	700 LBS.	700 LBS.
FLOOR SPACE REQUIRED			
HEIGHT	66"	66"	66"
WIDTH	54"	54"	73"
LENGTH: DOOR OPEN	80"	80"	80"
DOOR CLOSED	60"	65"	65"
TURNTABLE HEIGHT (ABOVE FLOOR)	27"	27"	27"
SHIPPING WEIGHT	1400 LBS	1600 LBS	1800 LBS
CLEANING SYSTEM			
SOLUTION CAPACITY	110 gals.	140 gals.	160 gals
PUMP MOTOR	7.5 HP	7.5 HP	7.5 HP
PUMP OUTPUT	70 psi @ 100 gpm	70 psi @ 100 gpm	70 psi @ 100 gpm
SPRAY NOZZLES	20 alternating	20 alternating	20 alternating
FILTER SCREEN	1200 sq."	1450 sq."	2530 sq."
CABINET CONSTRUCTION			
GAUGE STEEL	12 GA.INNER/16 GA.OUTER	12 GA.INNER/16 GA.OUTER	12 GA.INNER/16 GA.OUTER
INSULATION	1" fiberglass	1" fiberglass	1" fiberglass
STEAM VENT	6"	6"	6"
GAS VENT	6"	6"	6"
HEAT SOURCE			
ELECTRIC ELEMENT	12 kw	12 kw	15 kw
GAS BURNER	100,000 BTU	100,000 BTU	150,000 BTU
HOT TANK BASKETS			
WIDTH (I.D.)	13"	24"	24"
LENGTH (I.D.)	34"	34"	55"
DEPTH (I.D.)	11"	11"	11"
ELECTRICAL REQ.			
PUMP MOTOR 3 PHASE	208 / 230 / 460 Volts 21 18 9.4 Amps		
ELECTRICAL HEAT 3 PHASE	(12 KW) 208/230/460 Volts 33-29-17 Amps	(12 KW) 208/230/460 Volts 33-29-17 Amps	(15 KW) 208/230/460 Volts 41-37-19 Amps
*ELECTRICAL OPTIONS			
PUMP MOTOR 1 PHASE	230 Volts, 33 Amps		
ELECTRIC HEATER 1 PHASE	(12 KW) 230 Volts 52 Amps	(12 KW) 230 Volts 52 Amps	(15 KW) 230 Volts 65 Amps
STANDARD EQUIPMENT			
LOW WATER SWITCH	STANDARD		
DUAL 7 DAY TIMERS	STANDARD		
DIGITAL TEMP CONTROLLER	STANDARD		
HEAD RACK/CRANK RACK	STANDARD		
AUTO AIR INDUCER	STANDARD		
SHORT CIRCUIT PROTECTION	STANDARD		
THERMAL PROTECTION	STANDARD		
LAY DOWN DOOR/SEALESS	STANDARD		
V-BOTTOM FLOOR	STANDARD		
BUILT IN HOT TANK	STANDARD		
360 DEGREE MANIFOLD	STANDARD		
WARRANTY	ONE YEAR		
1" INSULATION	STANDARD		